

MP3 500 HPE SPORT ADVANCED - TECHNICAL SPECIFICATIONS

DISPLACEMENT493BORE X STROKE94	STER hpe single-cylinder, 4 stroke 3 cc mm x 71 mm
BORE X STROKE 94	
	mm x 71 mm
POWER 32	
	kW (43,5 CV) @ 7,750 rpm
TORQUE 47.	5 Nm @ 5,750 rpm
rolle	gle overhead cam shaft (SOHC) with 4 valves and er tappets
FUEL SYSTEM Ele	ctronic injection
with the for Dua Tra	ctronic n inductive exhaust and variable advance integrated in injection CPU. Closed loop system with Lambda probe the exhaust. Electronic immobilizer, block of injection np when the vehicle is tilted. Twin spark ignition. al map for throttle valve management (STD and ECO). cton control (ASR)
	t sump
COOLING SYSTEM Liqu	
	ctric
(rev	T continuously variable transmission with torque server verse gear on the Sport Advanced version) omatic centrifugal dry clutch
	uble cradle in high strength tubular steel
	l/100 km
	g/km
HOMOLOGATION Eur	-
FRONT SUSPENSION Arti	culated quadrilateral - Stroke: 85 mm. Electro- Iraulic suspension blocking system.
REAR SUSPENSION Dou pos with and	uble hydraulic shock absorber with four- ition spring pre-load adjustment (double gas shock n continuous spring pre-load adjustment on the Sport I Sport Advanced versions) - Stroke: 108 mm
	uble disc Ø 258 mm
	c Ø 240 mm
BRAKING SYSTEM ABS	S with braking integrated with the pedal
LENGHT/WIDTH/WHEELBASE 2,2	00 mm/800 mm/1,540 mm
SEAT HEIGHT 790) mm
FUEL TANK CAPACITY 13,	2 litres
WEIGHT IN RUNNING CONDITION 282	2 kg